

Refrigerated Snack Cabinet

Model	Ext. Dimension W×D×H (mm)	Int. Dimension W×D×H (mm)	Capacity (L)	Temperature (°C)	Shelf	Power Supply	Gross Weight (Kg)	Net Weight (Kg)
SNACK400TN V	680×700×2010	564×570×1390	500	-2 ~ +8°C	3 pcs	230V/50Hz	145	135
SNACK400BT V	680×700×2010	564×570×1390	500	-18 ~ -22°C	3 pcs	230V/50Hz	145	135
SNACK400TNM V	680×700×2010	564×570×1390	500	-2 ~ +8°C	3 pcs	230V/50Hz	145	135
SNACK400BTM V	680×700×2010	564×570×1390	500	-18 ~ -22°C	3 pcs	230V/50Hz	145	135
SNACK800TN V	1340×700×2010	1224×570×1390	967	-2 ~ +8°C	6 pcs	230V/50Hz	185	165
SNACK800BT V	1340×700×2010	1224×570×1390	967	-18 ~ -22°C	6 pcs	230V/50Hz	188	168
SNACK800TNM V	1340×700×2010	1224×570×1390	967	-2 ~ +8°C	6 pcs	230V/50Hz	185	165
SNACK800BTM V	1340×700×2010	1224×570×1390	967	-18 ~ -22°C	6 pcs	230V/50Hz	188	168
SNACK800TNM/2 V	1340×700×2010	1224×570×1390	967	-2 ~ +8°C	6 pcs	230V/50Hz	185	165
SNACK800BTM/2 V	1340×700×2010	1224×570×1390	967	-18 ~ -22°C	6 pcs	230V/50Hz	188	168
SNACK400TN	680×700×2010	564×570×1390	500	-2 ~ +8°C	3 pcs	230V/50Hz	145	135
SNACK400BT	680×700×2010	564×570×1390	500	-10 ~ -20°C	3 pcs	230V/50Hz	145	135
SNACK400STN	680×700×1940	564×570×1390	500	-2 ~ +8°C	3 pcs	230V/50Hz	140	130
SNACK400SBT	680×700×1940	564×570×1390	500	-10 ~ -20°C	3 pcs	230V/50Hz	140	130



SNACK400TNM V
SNACK400BTM V



SNACK800TNM V
SNACK800BTM V



SNACK800TNM/2 V
SNACK800BTM/2 V



SNACK400STN
SNACK400SBT