




Features

- CFC free refrigerant and foam
- Complete structure interior & exterior in stainless steel AISI 304 with round internal edges for easy cleaning
- Insulation 60 mm thickness
- Ventilated refrigeration compartment gives a better air circulation
- Auto defrosting and auto evaporation of condensation water
- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- Self-closing door
- Magnetic gasket can be replaced without any tools
- Heating element conceal in door frame to eliminate any condensation
- Designed to accommodate 1 number of GN 1/1 in pan size







C-GN3100TN / C-PA3100TN

Model	Ext. Dimension W×D×H (mm)	Int. Dimension W×D×H (mm)	Capacity (L)	Temperatur (°C)	e Shelf	Power Supply	Gross Weight (Kg)	Net Weight (Kg)
C-GN2100TN	1360×700×860	795×560×589	216	-2 ~ +8°C	2 pcs	230V/50Hz	113	98
C-GN3100TN	1795×700×860	1230×580×589	324	-2 ~ +8C	3 pcs	230V/50Hz	152	134
C-PA2100TN	1510×800×860	945×660×589	390	+2 - +8°C	400×600 mm 2 pcs	230V/50Hz	155	140
C-PA3100TN	2020×800×860	1455×660×589	580	+2 ~ +8°C	400×600 mn 3 pcs	230V/50Hz	170	152