

Ventilated Refrigerated Cabinet Unit Down Series

Features

- CFC free refrigerant and foam
- · Electronic thermostat and digital LED temperature display for accurate control and easy reading
- Self-closing door
- Magnetic gasket can be replaced without any tools
- Heating element conceal in door frame to eliminate any condensation







2010R / 2010F

2020R / 2020F

2030R / 2030F

Model	Ext. Dimension W×D×H (mm)	Int. Dimension W×D×H (mm)	Capacity (L)	Temperature (°C)	Shelf	Power Supply	Gross Weight (Kg)	Net Weight (Kg)
2010R	680×830×2100	564×700×1276	589	0 ~ +5°C	3 pcs	230V/50Hz	139	128
2010F	680×830×2100	564×700×1276	589	-1822°C	3 pcs	230V/50Hz	149	138
2020R	1370×830×2100	1254×700×1276	1306	0 ~ +5°C	6 pcs	230V/50Hz	222	207
2020F	1370-830-2100	1254×700×1276	1306	-18 ~ -22°C	6 pcs	230V/50Hz	227	212
2030R	2057×830×2100	1941×700×1276	2023	0 ~ +5°C	9 pcs	230V/50Hz	271	243
2030F	2057×830×2100	1941×700×1276	2023	-18 ~ -22°C	6 pcs	230V/50Hz	283	255